

DEVCOM

MANUFACTURING LLC



Super Heavy Duty Premium Sound Control Membrane Plus Crack Suppression - GS-12000SCM

100% MADE IN THE USA WITH OUR PATENTED "GO-GREEN" CONSTRUCTION DESIGNS

Hands Down, This is the Ultimate Peel and Stick Sound Control Membrane on the Market!!

Engineered to Provide the Highest Levels of Insulation Against Annoying Impact & Airborne Generated Sound Transmissions Via Our PATENTED "ECO-CORE™" Technology...SAY NO! to "Well, Just Add More Glue" Sound Control Solutions

Premium Water Resistant, Recycled Sound Control PLUS Crack Suppression/Isolation Membrane

Save Time and Money w/ our 100% Super Aggressive Primerless Chemistry – Simply Sweep!

OUR 1-2 COMBO PUNCH is our Super Hi-Strength Patented Antimicrobial/Non-Wicking Design plus our 40% Lighter Weight Construction vs. Typical Noxious Asphalt Membrane Designs

Patented Elastomeric Glue Design Provides Up To 1/2" Crack Strength (Tile Tester)

Guaranteed Zero Moisture Wicking for the Ultimate in Water Resistance/Protection

E-Z Peel Self Adhered/Peel and Stick Technology for Silky Smooth Tear Resistant Liner Release

120 mills thick - Self Adhered/Peel and Stick - Clean & Green Patented Design Front to Back

Super-Aggressive Crystal Clear Hot Melt PSA Adhesive w/ Zero VOC's/Solvents

9 Layer Membrane Construction w/ Hi-Strength Insulating Water Tight METPET Core

Maximum Water Resistance/Protection via our Patented HYDRO-SEAL™ Butt-Seam/Joint Design

Highly Reflective/Super Energy Efficient/METPET Insulated Core

Zero Light Transmission Provides Maximum Adhesive Protection Against UV/IR – 100% Opaque

70% + Recycled/Reclaimed Content by Weight – Fully Sustainable

Standard Adhesive Color/Tint: Crystal Clear

Standard Membrane Colors: "GO-Green"/Metallic - Personalized/Private Label Designs Available on All T/L Orders

WE ARE VERY PRICE COMPETITIVE! WE DO NOT UPCHARGE FOR OUR GO-GREEN DESIGNS!



Made with Pride in the Heartland of the USA!

Corporate Office

111 West Port Plaza Drive, Suite 600 / St. Louis, MO 63146

Corporate Office: 866.DEVCOM1 (338.2661) / **Scott Ford (direct):** 503.849.4106 / **e:** sford@devcomtape.com / **w:** devcomtape.com

DEVCOM

MANUFACTURING LLC



Super Heavy Duty Premium Sound Control Membrane Plus Crack Suppression - GS-12000SCM

Applicable Testing Procedures:

Adhesion to Plywood: ASTM D903 = 4.25 lbs/in width

Tensile Strength MD: ASTM D882 = 319 Lb/In-Width – TD: ASTM D882 = 343 Lb/In-Width

Tear MD: ASTM D1922 = 10,912 Grams – TD: ASTM D1922 = 11,906 Grams

Elongation at Break: ASTM D412 = 500% Minimum

Application Temperature = 15 deg F – 140 deg F

Service Temperature = -15 deg F – 215 deg F

****Sound Transmission Class: ASTM E90 = STC 59**

****Impact Insulation Class: ASTM E492 = IIC 52 (delta=24)**

Robinson Flooring: ASTM C627 = Extra Heavy Commercial Rating (successfully completed cycles 1-14)

Puncture: ASTM E154 = 282 Lbs

Water Vapor Transmission Rate: ASTM E 96-53 (Method E) = .00012 perms

****All Sound Testing Performed at Riverbank Labs, in Geneva, IL. Testing conditions as follows:
OVER A 6" SLAB – WITH NO DROP CEILING ASSEMBLY**



Made with Pride in the Heartland of the USA!

Corporate Office

111 West Port Plaza Drive, Suite 600 / St. Louis, MO 63146

Corporate Office: 866.DEVCOM1 (338.2661) / **Scott Ford (direct):** 503.849.4106 / **e:** sford@devcomtape.com / **w:** devcomtape.com