



Product - Devcom Horizontal Seam Tape ST-DC800

3 Layer Poly Film Construction – High Opacity

High Strength w/ EXCELLENT TEAR & PUNCTURE STRENGTH!

Horizontal Use Only – **DO NOT USE AS A WINDOW TAPE**

Recycled/Reclaimed Content

Standard Facer Colors: White-Gray/Carbon Back “C” layer

Personalized Logo Design on our Films featuring our Custom “Your Logo Here” Program

Standard Adhesive Color/Tint: Clear

Solubility to Water: Insoluble

Applicable Testing Procedures:

ASTM E 1643 - Standard Practice for Installation of Water Vapor Retarders

ASTM D 1000 - Standard Test Method for Pressure-Sensitive Adhesive Coated Tape Membranes

U.V. Protection: Excellent @ 6-12 Months U.V. Exposure

Cold Temperature Flexibility: ASTM C765-73 = Pass

Tensile Strength MD: ASTM D882 = 31 Lb/In-Width – TD: ASTM D882 = 35 Lb/In-Width

Tear MD: ASTM D1922 = 1,653 Grams – TD: ASTM D1922 = 1,874 Grams

Elongation at Break = 100% Minimum

Adhesion = 56 oz/In-Width

Puncture: ASTM E154 = 46 Lbs

Water Vapor Transmission Rate: ASTM E 96-53 (Method E) = .211 perms



Made with Pride in the Heartland of the USA!

Corporate Office

111 West Port Plaza Drive, Suite 600 / St. Louis, MO 63146

Corporate Office: 866.DEVCOM1 (338.2661) / **Scott Ford (direct):** 503.849.4106 / **e:** sford@devcomtape.com / **w:** devcomtape.com