



Product - Devcom Window & Door Flashing Tape WD-DC2500

Clean & Green Patented Design Front to Back w/ Zero VOC's/Solvents

9 Layer Construction w/ Hi-Tech Insulating Core – Highly Reflective/Energy Efficient

Super High Strength w/ a Virtual Tear-Stretch-Shrink-Curl Proof Design

Zero Light Transmission – 100% Opaque

Recycled/Reclaimed Content – Fully Sustainable

Standard Facer Colors: Silver Metallic, Green Metallic (others available upon request)

Personalized Logo Design on our Films featuring our Custom "Your Logo Here" Program

Standard Adhesive Color/Tint: Amber

Solubility to Water: Insoluble

Applicable Testing Procedures:

U.V. Protection: 48-60 Months

Sealant Compatibility: Proposed AAMA 700 Flashing = Pass

Environmental Affects on Peel/Heat Distortion: AAMA 711-05 Level 3 = Pass

Plasticizer Migration: ASTM C772-74 = Zero Transfer

Self Seal: ASTM D1970 Section 7.9 = Pass

Advanced Aging: ASTM D750-68 @ 5000 hrs = No notable change in Membrane or Adhesive

Cold Temperature Flexibility: ASTM C765-73 = Pass

Tensile Strength MD: ASTM D882 = 149 Lb/In-Width – TD: ASTM D882 = 163 Lb/In-Width

Tear MD: ASTM D1922 = 3,688 Grams – TD: ASTM D1922 = 3,976 Grams

Elongation at Break = 100% Minimum

Puncture: ASTM E154 = 126 Lbs

Water Vapor Transmission Rate: ASTM E 96-53 (Method E) = .0011 perms



Made with Pride in the Heartland of the USA!

Corporate Office

111 West Port Plaza Drive, Suite 600 / St. Louis, MO 63146

Corporate Office: 866.DEVCOM1 (338.2661) / **Scott Ford (direct):** 503.849.4106 / **e:** sford@devcomtape.com / **w:** devcomtape.com